

11 August 1998

AGREEMENT

**CONCERNING THE ADOPTION OF UNIFORM TECHNICAL PRESCRIPTIONS
FOR WHEELED VEHICLES, EQUIPMENT AND PARTS WHICH CAN BE FITTED AND/OR
BE USED ON WHEELED VEHICLES AND THE CONDITIONS FOR RECIPROCAL RECOGNITION
OF APPROVALS GRANTED ON THE BASIS OF THESE PRESCRIPTIONS ^{*}/**

(Revision 2, including the amendments entered into force on 16 October 1995)

Addendum 4: Regulation No. 5

Revision 3 - Amendment 2

Supplement 4 to the 02 series of amendments - Date of entry into force: 27 April 1998

**UNIFORM PROVISIONS FOR THE APPROVAL OF MOTOR VEHICLE "SEALED BEAM" HEADLAMPS (SB)
EMITTING A EUROPEAN ASYMMETRICAL PASSING BEAM OR A DRIVING BEAM OR BOTH**



UNITED NATIONS

^{*}/ Former title of the Agreement:

Agreement Concerning the Adoption of Uniform Conditions of Approval and Reciprocal Recognition of Approval for Motor Vehicle Equipment and Parts, done at Geneva on 20 March 1958.

GE.98-22727

Paragraph 5.2.1.1., footnote 1/, amend to read:

"1/ 30 (vacant), 31 for Bosnia and Herzegovina, 32-36 (vacant), 37 for Turkey, 38-39 (vacant) and 40 for The former Yugoslav Republic of Macedonia. Subsequent numbers to the Agreement Concerning the Adoption of Uniform Technical Prescriptions for Wheeled Vehicles, Equipment and Parts which can be Fitted and/or be Used on Wheeled Vehicles and the Conditions for Reciprocal Recognition of Approvals Granted on the Basis of these Prescriptions, ..."

Annex 5, paragraph 1.2.1.1., replace by the following text (including also a new footnote 4/):

"1.2.1.1. Test mixture

1.2.1.1.1. For headlamp with the outside lens in glass:

The mixture of water and a polluting agent to be applied to the headlamp shall be composed of:

9 parts by weight of silica sand with a particle size of 0-100 μm ,

1 part by weight of vegetal carbon dust (beechwood) with a particle size of 0-100 μm ,

0.2 part by weight of NaCMC 1/, and

an appropriate quantity of distilled water, with a conductivity of $\leq 1 \text{ mS/m}$.

The mixture must not be more than 14 days old.

1.2.1.1.2. For headlamp with outside lens in plastic material:

The mixture of water and polluting agent to be applied to the headlamp shall be composed of:

9 parts by weight of silica sand with a particle size of 0-100 μm ,

1 part by weight of vegetal carbon dust (beechwood) with a particle size of 0-100 μm ,

0.2 part by weight of NaCMC 1/, and

13 parts by weight of distilled water with a conductivity of $\leq 1 \text{ mS/m}$, and

2 ± 1 parts by weight of surface-actant. 4/

The mixture must not be more than 14 days old.

-
- 3/ (note not modified)
4/ The tolerance on quantity is due to the necessity of obtaining a
dirt that correctly spreads out on all the plastic lens."

Paragraph 1.2.1.2... reference to footnote 4/ and footnote 4/, renumber as
footnote 5/.
